



# Generating sets

## GALAXIE - Soundproof

Generating sets Open	Engine Make and Type	Regulation Cylinders Aspiration	Alternator	Frequency 50 Hz (kVA)		Dimensions	Weight	Fuel Tank Capacity Autonomy
				PRP	ESP			
GES6M-12v	KOHLER KDW702	M - 0,7 L - 2 cyI -NA	E1X13SB/4	6	6,6	180 x 75 x 120 cm	410 kg	50L / 42h
GES11M-12v	KOHLER KDW1003	M - 1 L - 3 cyI -NA	E1X13SC/4	9	10	180 x 75 x 120 cm	500 kg	50L / 31h
GES15M-12v	KOHLER KDW1404	M - 1,4 L - 4 cyI -NA	E1X13ME4	13	14	180 x 75 x 120 cm	550 kg	50L / 21h
GES20M-12v	KOHLER KDW1603	M - 1,6 L - 3 cyI -NA	E1X13MF4	16	17,5	180 x 75 x 120 cm	600 kg	50L / 16h
GES22M-12v	KOHLER KDI1903	M - 1,9 L - 3 cyI -NA	SLT18MD	20	22	180 x 75 x 120 cm	750 kg	50L / 10h
GES25M-12V	KOHLER KDI2504M	M - 2,5 L - 4 cyI - NA	PRO 18SB/4	25	27	226 x 91 x 160 cm	980 kg	100L / 18h
GES30M-12v	IVECO F32AM1	M - 3,2 L - 4 cyI -NA	PRO 18SC/4	30	33	226 x 91 x 160 cm	980 kg	100L / 15h
GES31M-12v	KOHLER KDI2504TM	M - 2,5 L - 4 cyI -TCA	PRO 18SC/4	30	33	226 x 91 x 160 cm	980 kg	100L / 18h
GES40M-12v	IVECO F32SM1	M - 3,2 L - 4 cyI -TC	PRO 18ME/4	40	44	226 x 91 x 160 cm	1230 kg	100L / 12h
GES50M-12v	IVECO F32TMA	M - 3,2 L - 4 cyI -TC	PRO 18LF/4	50	55	226 x 91 x 160 cm	1250 kg	100L / 10h
GES55M-12v	KOHLER KDI3404TMAC	M - 3,4 L - 4 cyI -TC	PRO 18LG/4	55	60	226 x 91 x 160 cm	1250 kg	100L / 9h
GES60MNEF-12v	IVECO N45SM1	M - 4,5 L - 4 cyI -TC	PRO 18LG/4	60	66	226 x 91 x 160 cm	1300 kg	200L / 23h
GES75MNEF-12v	IVECO N45SM2	M - 4,5 L - 4 cyI -TC	PRO 22SB/4	75	84	226 x 91 x 160 cm	1540 kg	200L / 16h
GES85MNEF-12v	IVECO N45TM1	M - 4,5 L - 4 cyI -TCA	PRO 22SC/4	85	94	286 x 110 x 195 cm	1620 kg	200L / 14h
GES100MNEF-12v	IVECO N45TM2	M - 4,5 L - 4 cyI -TCA	PRO 22SD/4	100	110	286 x 110 x 195 cm	1900 kg	200L / 12h
GES130MNEF-12v	IVECO N67TM3	M - 6,7 L - 6 cyI -TCA	PRO 22ME/4	130	143	350 x 117 x 220 cm	2000 kg	250L / 10h
GES150MNEF-12v	IVECO N67TM3	M - 6,7 L - 6 cyI -TCA	PRO 22MF/4	150	165	350 x 117 x 220 cm	2360 kg	250L / 9h
GES160MNEF-12v	IVECO N67TM3	M - 6,7 L - 6 cyI -TCA	PRO 28SA/4	160	176	350 x 117 x 220 cm	2360 kg	250L / 9h
GES200ENEf-12v	IVECO N67TE2	E - 6,7 L - 6 cyI -TCA	PRO 28SB/4	200	220	350 x 117 x 220 cm	2580 kg	250L / 8h
GES250ECUR-24v	IVECO C87TE2	E - 8,7 L - 6 cyI -TCA	PRO 28SD/4	250	275	430 x 155 x 225 cm	3250 kg	600L / 13h
GES275ECUR 24v	IVECO C87TE2	E - 8,7 L - 6 cyI -TCA	PRO 28ME/4	275	300	430 x 155 x 225 cm	3250 kg	600L / 13h
GES300ECUR-24v	IVECO C10TE1	E - 10,3 L - 6 cyI -TCA	PRO 28ME/4	300	330	430 x 155 x 225 cm	4150 kg	600L / 11h
GES350ECUR-24v	IVECO C13TE2	E - 12,9 L - 6 cyI -TCA	PRO 28MF/4	350	385	430 x 155 x 225 cm	4660 kg	600L / 10h
GES400ECUR-24v	IVECO C13TE3	E - 12,9 L - 6 cyI -TCA	PRO 28LG/4	400	440	430 x 155 x 225 cm	4780 kg	600L / 9h

## GALAXIE Soundproof

**Generating sets  
Soundproof  
Emission standards:  
Stage II / SDT CE**

**230/400 V - 50 Hz - 4 P  
1500 rpm  
Altitude max 1000m  
Liquid cooling**

Equipment:

Engine and alternator mounted with SAE coupling discs, squid fitted with anti-vibration wedging blocks.

Control panel 12v or 24v with: key switch start, engine emergency shut down, voltmeter, frequency meter, ammeter, emergency stop button, hour meter, circuit breaker, power terminal.

Galvanised welded steel squid, soundproof canopy, epoxy paint, lifting eye. Built-in fuel tank, locking cap, filters

Sound proof canopy: Residential silencer, lockable side doors, stone wool, epoxy - 65 dB(A) at 7 meters.

Automatic transfer switch units: Automatic start (external dry contact, over and under frequency, over and under voltage input and output terminal junction, electrical and mechanical security).

Earth leakage protection 30 mA or 300 mA (up to 125 AMP)

30 mA if the group is equipped with plugs

Adjustable earth leakage protection (above 125AMP)

Identification plate.

Start-up and maintenance guide in English

Units are built in compliance with standards ISO8528 - 89/336 - 92/31 - 93/68 - 98/37 - 98/79 - 04/26 (CEE)



**2 GARENI INDUSTRIE**  
Rue des écoles  
47600 CALIGNAC  
FRANCE

Tel: +33(0) 5 53 65 80 40  
Fax: +33(0) 5 53 65 88 73 / +33(0) 5 53 65 69 20  
contact@2gareni-industrie.com  
www.2gareni-industrie.com

Warranty: 12 months, according to our Terms and Conditions and under normal use conditions (after a series of tests), on spare parts found faulty by 2 Gareni Industrie technical services. We offer a 60 months extended warranty. Prices apply until: 15/09/2015. Prices are indicated without taxes, without transport, except errors and missing. Prices may change at any time. Pictures weights and heights are non-contractual. In accordance with company policy of continuous improvement, alterations to products and specifications may differ from those stated in this publication.